

16 CH 3in1 + 8 CH IP Hybrid DVR

SA-16200AHD-2 (1U)+



1080P Lite 1080P 1080P 3MP



MODEL		SA-16200AHD-2(1U)+	
System	Compression Format	High profile H.264	
	ONVIF	Yes (For IP Channels)	
	Format	Tribrid AHD / TVI / CVBS + IP	
Video	Input	16CH Standard BNC + 8CH IP (Over Network)	
	Standard Output	HDMI, VGA (1024x768), CVBS (Spot)	
Audio	Input	4CH	
	Output	1CH	
	Two Way Audio	Yes	
Recording	AHD + TVI	Real-Time Recording	16CH 1080P Half Real-Time
		2MP (1080P)	240FPS (NTSC)/200FPS (PAL). Up to 15/12FPS Per Channel
		2MPL (1080P Lite)	480FPS (NTSC)/400FPS (PAL)
		1MP (720P)	480FPS (NTSC)/400FPS (PAL)
	Analog	Real-Time Recording	16CH 960H Real-Time
		960H	480FPS (NTSC)/400FPS (PAL)
		D1	No
		CIF	No
	IP	Real-Time Recording	8CH 1080P Real-Time
		3MP	180FPS (NTSC)/150FPS (PAL) Total.
		2MP (1080P)	240FPS (NTSC)/200FPS (PAL)
		1.3MP (960P)	240FPS (NTSC)/200FPS (PAL)
		1MP (720P)	240FPS (NTSC)/200FPS (PAL)
	General	Recording Modes	Schedule, Manual, Motion, Sensor
Playback	AHD/TVI/CVBS Playback		8CH
	IP Playback		1CH
	Search Mode		Time, Event, File Management
Backup	USB		2 USB 2.0 Port
	DVD Burner		Optional
	Backup Format		AVI/DAT
Remote Application	AHD Stream		Master Stream 1-25/30FPS@720P/1080P Lite / 1-12/15FPS@1080P; Sub-Stream: Up to 1-25FPS@720P
	Analog Stream		Master & Sub-Stream 1-25/30FPS@960H
	IP Stream		Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1
	Master Stream		Up to 4Ch@Recording Resolution
	Browser		IE, Safari, Firefox (Mac OS, Windows XP/Vista/7/8/10)
	CMS		Yes
	Mobile Application		Provision Cam2 for iOS/Android
Alarm	User Access		10 Users Online with Professional Authority Management
	Input	4CH	
	Output	1CH	
Storage	HDD	2 SATA (6TB Each)	
	E-SATA	No	
PTZ	Connection	RS-485 / CoC / IP-Over Network	
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC	
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus	
Network	Ethernet	100 Mbps (RJ-45)	
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P	
Others	Dimension	W375xD275xH45mm	
	IR Controller	Yes	
	Power Supply	DC12V/4A	
	Operation Temperature	0°C ~50°C	